

Type	Size	Standard	Material	Gasket	O-ring	Diaphragm	End type	Bolt
VP-710	1/2"~8"	ANSI, JIS, DIN	PVC	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316
VP-711	1/2"~8"	ANSI, JIS, DIN	CPVC	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316
VP-713	1/2"~8"	ANSI, JIS, DIN	PVDF	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316
VP-714	1/2"~8"	ANSI, JIS, DIN	PP	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316

- **Pressure rating: 1/2"~3" 100 PSI, 4"~6" 72 PSI, 8" 43 PSI**
- **Smooth and exact operation with clear indication of opening degree**
- **Low maintenance cost with replaceable diaphragm and long service life**
- **Adjustable stopper can avoid over tightening**
- **Easy to install and set with flat zone design at the bottom of flange**
- **Stem / Sleeve can adopt SUS 304 / 316L for corrosive environment**



Caution! The valve is completely closed when handwheel can't turn more with normal torque, but it will cause the unrecoverable divulsion of diaphragm if the handwheel is continuously forced to turn in such above condition!

Additional catalogue cards with all dimensions on request [send e-mail](#)