

Type	Size	Standard	Material	Gasket	O-ring	Diaphragm	End type	Bolt
VP-720	1/2"-2"	DIN	PVC	EPDM	NBR	EPDM, FPM, PTFE	Spigot	SUS 304 / 316
VP-721	1/2"-2"	DIN	CPVC	EPDM	NBR	EPDM, FPM, PTFE	Spigot	SUS 304 / 316
VP-723	1/2"-2"	DIN	PVDF	EPDM	NBR	EPDM, FPM, PTFE	Spigot	SUS 304 / 316
VP-724	1/2"-2"	DIN	PP	EPDM	NBR	EPDM, FPM, PTFE	Spigot	SUS 304 / 316
VP-730	1/2"-2"	ANSI, JIS, DIN	PVC	EPDM	NBR / EPDM, FPM	EPDM, FPM, PTFE	Socket, Threaded	SUS 304 / 316
VP-731	1/2"-2"	ANSI, JIS, DIN	CPVC	EPDM	NBR / EPDM, FPM	EPDM, FPM, PTFE	Socket, Threaded	SUS 304 / 316
VP-733	1/2"-2"	ANSI, JIS, DIN	PVDF	EPDM	NBR / EPDM, FPM	EPDM, FPM, PTFE	Socket, Threaded	SUS 304 / 316
VP-734	1/2"-2"	ANSI, JIS, DIN	PP	EPDM	NBR / EPDM, FPM	EPDM, FPM, PTFE	Socket, Threaded	SUS 304 / 316

- **Pressure rating: 100 PSI**
- **Smooth and exact operation with clear indication of opening degree**
- **Low maintenance cost with replaceable diaphragm and long service life**
- **Adjustable stopper can avoid over tightening**
- **Easy to fix with inserted nut at the bottom of valve**
- **Stem / Sleeve can adopt SUS 304 / 316L for corrosive environment**



**Caution! The valve is completely closed when handwheel can't turn more with normal torque, but it will cause the unrecoverable divulsion of diaphragm if the handwheel is continuously forced to turn in such above condition!**