


PISTON CHECK VALVE

GT-P TYPE SIZE: 1/4" ~ 2"

- FEATURES:**
- * Investment casting body & cap.
 - * 300 PSI (20 BAR) W.O.G. rating.
 - * Maximum working temperature 230° C.
 - * The end-to-end length conforms to Din 3202, Part 4, M8 series. (PN40)
 - * Thread ends conform to ANSI B2.1, BS2.1, DIN 259/2999 STANDARD



ITEM	PARTS	MATERIALS
1	BODY	ASTM-A351-CF8M
2	CAP	ASTM-A351-CF8M
3	SPRING	AISI 316
4	DISC	AISI 316
5	SEAT	PTFE
6	WASHER	AISI 304
7	NUT	AISI 304
8	JOINT GASKET	PTFE



SIZE	d	L	S	H	W
1/4"	11.6	65.5	27	38	24
3/8"	12.5	65.5	27	38	24
1/2"	12.5	65.5	27	36	24
3/4"	18	75.5	32	44	30
1"	23.5	90.5	41	57	35
1-1/4"	31.4	111	50	64	40
1-1/2"	35.7	121	55.5	76	45
2"	45.5	151	70	87	55

CLASS 200 SWING CHECK VALVE

SCREWED END

GT-C TYPE SIZE: 1/2" ~ 2"

Full port pressure temperature rating 200 PSI W.O.G.
350° F S.P. threaded ends conform to ANSI B 2.1, BS 21,
DIN 259/2999, Stainless steel class 200 screwed cap,
swing type disc, integral seat.



ITEM	PARTS	MATERIALS
1	BODY	ASTM-A351-CF8M
2	CAP	ASTM-A351-CF8M
3	DISC	AISI 316
4	HINGE PIN	AISI 316
5	PACKING	PTFE
6	PIPE PLUG	AISI 316

SIZE	d	L	S	H
1/4"	10	65	27	45
3/8"	12	65	27	45
1/2"	15	65	27	45
3/4"	20	80	34	55
1"	25	90	40	58
1-1/4"	32	105	50	62
1-1/2"	40	120	57	75
2"	50	140	70	78